

### Main

Range	PowerLogic
Product name	ComX
Product or component type	Energy server
Device short name	ComX 200


### Complementary

[Us] rated supply voltage	Main supply : 100...230 V - AC at 50/60 Hz Main or redundant power supply : 24 V - DC
Power consumption in W	<= 15 W via PoE <= 26 W 24 V <= 26 W 100...230 V
Communication network type	1 RJ45 : Ethernet, DHCP 1 RJ45 : Ethernet, PoE 15W (Power over Ethernet) Terminal block : RS485, Modbus serial 1 RJ45 : RS485, Modbus serial
Number of inputs	2 analog 6 digital
Discrete input current	60 mA at 12 V DC
Sensor power supply	24 V DC, 50 mA
Analogue input type	0...10 V 4...20 mA Pt 100 Pt 1000
Memory capacity	256 MB flash 128 MB RAM
Mounting mode	Clip-on
Mounting support	35 mm DIN rail
Product certifications	CE C-Tick
Standards	EN 60950 EN 61010-1
Depth	69 mm
Height	109 mm
Width	144 mm
Product weight	450 g
Local signalling	LED: for I/O LED: for communication (WiFi) LED: for communication (Ethernet) LED: for communication (Modbus) LED: for status (GPRS) LED: for power supply

## Environment

Relative humidity	5...95 % at 55 °C without condensation
IP degree of protection	Front face : IP40 Terminal block : IP20
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Pollution degree	3
Operating altitude	2000 m

## Offer Sustainability

Sustainable offer status	Not Green Premium product
Product environmental profile	Available
Product end of life instructions	Available  <a href="#">Download End Of Life Manual</a>