



Main

Range	PowerLogic
Product name	ComX
Product or component type	Energy server
Device short name	ComX 510

Complementary

[Us] rated supply voltage	Main supply : 24 V - DC
Power consumption in W	<= 15 W via PoE <= 26 W 24 V
Communication network type	1 RJ45 : Ethernet, DHCP 1 RJ45 : Ethernet, PoE 15W (Power over Ethernet) Terminal block : RS485, Modbus serial 1 RJ45 : RS485, Modbus serial
Number of inputs	2 analog 6 digital
Discrete input current	60 mA at 12 V DC
Sensor power supply	24 V DC, 50 mA
Analogue input type	0...10 V 4...20 mA Pt 100 Pt 1000
Memory capacity	4 GB SDRAM 256 MB flash 128 MB RAM
Mounting mode	Clip-on
Mounting support	35 mm DIN rail
Product certifications	CE C-Tick CUL UL
Standards	EN 60950 EN 61010-1 UL 508 UL 60950
Depth	69 mm
Height	109 mm
Width	144 mm
Product weight	450 g
Local signalling	LED: for I/O LED: for communication (WiFi) LED: for communication (Ethernet) LED: for communication (Modbus) LED: for status (GPRS) LED: for power supply

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Relative humidity	5...95 % at 55 °C without condensation
IP degree of protection	Front face : IP40 Terminal block : IP20
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Pollution degree	3
Operating altitude	2000 m