

resi-linx® Distribution made Easy.

resi-linx® Composite Stereo & IR RF Digital DVB-T Modulators

A 1124



These modulators and accessories allow the distribution of stereo audio and composite video (A 1121B also features component input) signals from a variety of sources. They enable AV signals from DVD, security camera, Pay TV etc to be transmitted over a single 75Ω coaxial cable. Each AV input can be assigned its own dedicated TV channel. It allows the connected sources to be viewed at multiple locations simultaneously, depending on the splitters used. Selecting the desired source is as simple as changing channels on your TV. The digi-MOD can also be used in commercial head-end installations allowing distribution of AV devices on desired DVB-T channels and integration into commercial installs. When combined with infra-red targets and emitters, each modulator allows full remote control of AV devices at the location of each television. Includes power supply.

Price Each	resi-linx® Part	RRP	2+
A 1121B 1 channel modulator	RL-DM1102M	479.00	469.00
A 1124 4 channel modulator	RL-DM4000	2100.00	1995.00
A 1119 Rack mounting ears	RL-ACC500	24.95	

resi-linx® HDMI RF Digital DVB-T Modulators

A 1128



This high definition, HDMI equipped, modulation system will allow you to distribute any HD devices (Foxtel, Astar, DVD etc) in true HD around the home or business with ease. Transmit sources to secondary locations over a single 75Ω coaxial cable. Each AV input can be assigned its own dedicated TV channel. It allows the connected sources to be viewed at multiple locations simultaneously, depending on the splitters used. Selecting the desired source is as simple as changing channels on your TV. This model supports MPEG-2 making it ideal for retrofit into installations with older TVs. Fan cooled design for commercial applications. Includes power supply.

Price Each	resi-linx® Part	RRP	2+
A 1126 1 channel modulator	HD-1000DM	2190.00	2080.00
A 1128 2 channel modulator	HD-2000DM	3390.00	3200.00

SPECIFICATIONS

	A 1121B	A 1124	A 1126	A 1128	A 1127	A 1130
Channels/inputs:	One	Four	One	Two	One	Four
Video input:	Composite (CVBS)/Component/S-Video	Composite (CVBS)	HDMI/Component/CVBS	HDMI/Component/CVBS	HDMI	HDMI/Component/CVBS
Audio input:	Stereo RCA	Stereo RCA	HDMI/Stereo RCA/Digital Coaxial/Optical	HDMI/Stereo RCA/Digital Coaxial/Optical	HDMI	HDMI/Stereo RCA/Digital Coaxial/Optical
Resolutions supported:	576i	576i	576i/720P/1080i/1080P	576i/720P/1080i/1080P	576i/720P/1080i/1080P	576i/720P/1080i/1080P
Output channels:	6 - 69	6 - 69	6 - 69	6 - 69	6 - 69	6 - 69
Output connector:	F-type	F-type	F-type	F-type	F-type/HDMI	F-type/HDMI
Output level:	95dB (20dB adj.)	95dB (20dB adjustment)	95dB (20dB adjustment)	95dB (20dB adjustment)	95dB (20dB adjustment)	95dB (20dB adjustment)
Video format:	MPEG-2	MPEG-2	MPEG - 2 / AVC (MPEG -4)	MPEG - 2 / AVC (MPEG -4)	AVC (MPEG -4)	MPEG - 2 / AVC (MPEG -4)
Infra-red return path:	Yes	Yes	No	No	Yes	No
Remote network setup:	Yes	Yes	Yes	Yes	Yes	Yes

resi-linx® Quad Input HDMI RF Digital DVB-T Modulator



This new high definition, HDMI equipped, modulation system will allow you to distribute any HD devices (Foxtel, Astar, DVD etc) in true HD around the home or business with ease. Transmit sources to secondary locations over a single 75Ω coaxial cable. Each AV input can be assigned its own dedicated TV channel. It allows the connected sources to be viewed at multiple locations simultaneously, depending on the splitters used. Selecting the desired source is as simple as changing channels on your TV. Ideal for retrofitting/upgrading older analogue modulator installations. Includes power supply.

Features • Converts HD video and audio signals to digital COFDM DVB-T channel • Dual mode - MPEG-2 & AVC (MPEG-4) encoding • Distributes 576i / 720P / 1080i / 1080P picture quality (1080P only available on AVC) • HDMI, component, CVBS & analogue audio inputs • Programmable; channel, network names and LCN • Full function front LCD for adjustments • Remote access and control GUI via web browser • Emergency announcement system control (EAS) input • Internal fan cooling system for long life span • 2K/8K carriers • Adjustable VHF / UHF output (6-69) • 20 dB adjustable attenuation (98dB launch) • 1RU rack mountable • Distributes on any new or existing RF cable

Price Each	resi-linx® Part	RRP	2+
A 1130 4 channel modulator	HD-4001DM	5100.00	4900.00

resi-linx® HDMI RF Digital DVB-T Loop Through Modulator



Suitable for use with digital TV. This new high definition, HDMI equipped, modulation system will allow you to distribute any HD devices (Foxtel, Astar, DVD etc) in true HD around the home or business with ease. It is identical in operation to the units shown left, with the addition of a HDMI loop output and infra-red return path. When combined with infra-red targets and emitters, each modulator allows full remote control of AV devices at the location of each television. Ideal for retrofitting/upgrading older analogue modulator installations. Includes power supply.

Price Each	resi-linx® Part	RRP	2+
A 1127 1 channel modulator with loop through	HD-1600	1155.00	1115.00
A 1119 Rack mounting ears	RL-ACC500	24.95	

For more information visit www.resi-linx.com

Complete installation diagrams, user manuals, brochures and more available from www.resi-linx.com.